

掘削機の適用範囲 (BK-10Ⅲ型～BK-23Ⅲ型)

単位(mm)

		軸 部 径																				
		1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000
掘削機	1000	1.00																				
	1100	1.00	1.00			BK-10Ⅲ																
	1200	1.21	1.00	1.00			BK-11Ⅲ															
	1300	1.44	1.19	1.00	1.00			BK-12Ⅲ														
	1400	1.69	1.40	1.17	1.00	1.00				BK-13Ⅲ												
	1500	1.96	1.62	1.36	1.16	1.00	1.00				BK-14Ⅲ											
	1600	2.25	1.86	1.56	1.33	1.15	1.00	1.00				BK-15Ⅲ										
	1700	2.56	2.12	1.78	1.51	1.31	1.14	1.00	1.00				BK-16Ⅲ									
	1800	2.89	2.39	2.01	1.71	1.47	1.28	1.13	1.00	1.00							BK-17Ⅲ					
	1900	3.24	2.68	2.25	1.92	1.65	1.44	1.27	1.12	1.00	1.00							BK-18Ⅲ				
	1950	3.42	2.83	2.38	2.03	1.75	1.52	1.34	1.18	1.06	1.00											
	2000	3.61	2.98	2.51	2.14	1.84	1.60	1.41	1.25	1.11	1.00	1.00								BK-19Ⅲ		
	2100	4.00	3.31	2.78	2.37	2.04	1.78	1.56	1.38	1.23	1.11	1.00	1.00								BK-20Ⅲ	
	2200		3.64	3.06	2.61	2.25	1.96	1.72	1.53	1.36	1.22	1.10	1.00	1.00								
	2300		4.00	3.36	2.86	2.47	2.15	1.89	1.67	1.49	1.34	1.21	1.10	1.00								BK-23Ⅲ
	2400			3.67	3.13	2.70	2.35	2.07	1.83	1.63	1.47	1.32	1.20	1.09	1.00	1.00						
	2500			4.00	3.41	2.94	2.56	2.25	1.99	1.78	1.60	1.44	1.31	1.19	1.09	1.00	1.00					
	2600				3.70	3.19	2.78	2.44	2.16	1.93	1.73	1.56	1.42	1.29	1.18	1.09	1.00	1.00				
	2700				4.00	3.45	3.01	2.64	2.34	2.09	1.87	1.69	1.53	1.40	1.28	1.17	1.08	1.00	1.00			
	2800					3.72	3.24	2.85	2.52	2.25	2.02	1.82	1.65	1.51	1.38	1.27	1.17	1.08	1.00	1.00		
	2900					4.00	3.48	3.06	2.71	2.42	2.17	1.96	1.78	1.62	1.48	1.36	1.25	1.16	1.08	1.00	1.00	
	3000						3.74	3.29	2.91	2.60	2.33	2.10	1.91	1.74	1.59	1.46	1.35	1.24	1.15	1.07	1.00	1.00
	3100						4.00	3.52	3.12	2.78	2.49	2.25	2.04	1.86	1.71	1.56	1.44	1.33	1.23	1.15	1.07	1.00
	3200							3.75	3.33	2.97	2.66	2.40	2.18	1.99	1.82	1.67	1.54	1.42	1.32	1.23	1.14	1.07
	3300							4.00	3.54	3.16	2.84	2.56	2.32	2.12	1.94	1.78	1.64	1.51	1.40	1.31	1.22	1.14
	3400								3.77	3.36	3.02	2.72	2.47	2.25	2.06	1.89	1.74	1.61	1.49	1.39	1.29	1.21
	3500								4.00	3.57	3.20	2.89	2.62	2.39	2.19	2.01	1.85	1.71	1.59	1.47	1.37	1.28
	3600									3.78	3.39	3.07	2.78	2.53	2.32	2.13	1.96	1.81	1.68	1.56	1.46	1.36
3700									4.00	3.59	3.24	2.94	2.68	2.45	2.25	2.07	1.92	1.78	1.65	1.54	1.44	
3800										3.79	3.42	3.10	2.83	2.59	2.38	2.19	2.03	1.88	1.75	1.63	1.52	
3900										4.00	3.61	3.27	2.98	2.73	2.51	2.31	2.14	1.98	1.84	1.72	1.60	
4000											3.80	3.45	3.14	2.88	2.64	2.43	2.25	2.09	1.94	1.81	1.69	
4100											4.00	3.63	3.31	3.02	2.78	2.56	2.37	2.19	2.04	1.90	1.78	
4200														3.18	2.92	2.69	2.49	2.31	2.14	2.00	1.87	
4300														3.33	3.06	2.82	2.61	2.42	2.25	2.10	1.96	
4400														3.50	3.21	2.96	2.74	2.54	2.36	2.20	2.05	
4500														3.66	3.36	3.10	2.86	2.66	2.47	2.30	2.15	
4600														3.83	3.52	3.24	3.00	2.78	2.58	2.41	2.25	
4700														4.00	3.67	3.39	3.13	2.90	2.70	2.52	2.35	

 : 施工範囲
 : 掘削機(BK-10Ⅲ型～BK-23型)適用範囲

表中の数値は確定率を示す(確定率=有効底面積÷軸部断面積)